



marine products

Capella[®] A 68



Description

Capella[®] A is a premium synthetic compressor oil specifically designed for the lubrication of ammonia refrigeration compressors operating at high discharge temperatures in systems with extremely low evaporator temperatures. Capella[®] A is formulated from specially synthesized polyalphaolefin (PAO) base fluids.

Typical Characteristics

ISO Viscosity Grade	68
MPID	21941
	5
Density 15°C, kg/l	0.83
Flash Point, °C	260
Pour Point, °C	-57
Viscosity, kinematic	
mm ² /s @ 40°C	68.7
mm ² /s @ 100°C	10.6
Viscosity Index	143
Acid No., mg KOH/g	0.01

Recommended Applications

Lubrication of compressors in refrigeration and air-conditioning systems filled with ammonia, especially where the minimum evaporator temperatures are down to -60°C. The product is particularly suited for reciprocating and screw ammonia compressors operating at discharge temperatures exceeding 100°C.

Capella A 68 Is Approved For:

- ABB Stal Refrigeration AB**
- Sabroe**
- Broedrene Gram**

Capella A 68 Meets The Requirements Of:

- DIN 51503**
- British Standard 2626/1992**



marine products

Performance Benefits

1. Efficient, Trouble-free Operation

Extremely low pour point and freon floc point (below -50°C) help enable fluidity without wax or deposit formation at very low minimum evaporator temperature, even with low solvency of the lubricating oil in the refrigerant. This further contributes to evaporator efficiency and cleanliness of the flow lines.

Synthetic polyalphaolefin base fluid provides a very low pour point (-57°C) and less oil thickening even at extremely low temperatures. This helps make the product suitable for operation at the very low evaporator temperatures typical in modern ammonia refrigeration systems, where in addition the solvency of the lubricating oil in the refrigerant is very low. Further, the low oil volatility of the synthetic polyalphaolefin base fluid reduces oil consumption and limits the amount of lubricant carry-over to the evaporator, which results in increased heat transfer efficiency. Additive free formulation prevents production of sludge caused by ammonia soap formation.

Low moisture content helps prevent icing in refrigeration expansion valves and deliver maximum corrosion protection.

2. Minimum Downtime

Synthetic polyalphaolefin base fluid provides excellent thermal and chemical stability in the presence of ammonia, avoiding the formation of gum, varnish and sludge deposits.

3. Lower Maintenance Costs

Ultra high viscosity index of synthetic polyalphaolefin base fluid helps provide highest oil viscosity at elevated operating temperatures and maintain fluid film strength for greatest protection against compressor wear.

4. Easier Cold Start-up

Ultra high viscosity index of synthetic polyalphaolefin base fluid helps provide lower viscosity at cold temperatures, reducing cold start-up power requirements.



Disclaimer. Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturers so always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS. (January 2024)