



marine lubricants

# Rust Proof Compound L



## Description

Rust Proof Compound L is a soft film rust preventive for relatively long-term protection of iron and steel components. Formulated from a high melting point petrolatum and a special rust inhibitor system with penetrating and water displacing capabilities. Rustproof Compound L® contains a petroleum solvent to make application easier.

## Typical Characteristics

Grade	L
MPID	219574
Colour	Dark Brown
Flash Point, COC, °C	85
Penetration, Undisturbed @ 25°C	280
Solvent Content, m %	20

## Recommended Applications

Application of Rust Proof Compound L can be used over rust, scale, paint or other rust proofing materials. However, it will be easier to apply, and long-term protection will be obtained if heavy rust and other deposits are removed prior to application. Rust Proof Compound L should not be heated above 55°C. If the required consistency cannot be obtained by heating, it can be thinned with Stoddard Solvent to any consistency for easy application. It can be applied via brush, drip or spray.

Rust Proof Compound L can be used on but not limited to the following; undercoating of vehicles, transformer casing, bridges and floating bridge pontoons, storage vessels (non-food), non-potable water tanks, ballast tanks, gas holders, hoisting equipment, farm implements, and iron and steel exposed to atmospheric conditions before, during and after manufacturing into finished parts.

Spraying of Rust Proof Compound L can be accomplished with conventional pressure-feed, air-atomizing spray equipment. Where indoor spraying is to be performed, the use of airless spraying equipment is recommended in well ventilated area. Rust Proof Compound L is not suitable for use on surfaces carrying pedestrian or vehicular traffic.

## Performance Benefits

### 1. Superior Long-term Rust Protection

Petrolatum and special additive system form a non-hardening, self-sealing film to protect surfaces against the elements. Good water displacing capabilities helps ensure that the protective film is also waterproof. The special rust inhibitor system ensures maximum protection against corrosive attack. Good penetrating characteristics ensure difficult-to-reach seams and crevices receive effective corrosion protection.

### 2. Requires Minimum Surface Preparation

Ability to penetrate existing flaky or heavy rust means that little or no preliminary cleaning of metal surfaces is required before application. This penetrating ability makes existing rust easier to remove.

### 3. Self-sealing Film

Self-sealing properties of the protective film minimizes the need for touch-ups when film damage occurs through scratches or brush marks.

### 4. Easy Removal

Soft protective film is readily soluble in petroleum solvent to enable easy removal when required.



## marine lubricants

**Environment, Health And Safety**

Information is available on this product in the Safety Data Sheet (SDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain an SDS for this product visit [chevronmarineproducts.com](http://chevronmarineproducts.com).



**Disclaimer.** Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturers so always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS. (May 2019)

© 2019 Chevron Marine Products LLC. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC or their respective owners.