

Delo[®] 1000 Marine



Description

Delo® 1000 Marine lubricants are high-performance diesel engine oils for medium-speed trunk piston diesel engines. Delo 1000 Maine lubricants are blended with highly refined base oils and carefully selected additives. They have very good viscosity control when used in severe high-temperature service, and their great BN retention characteristics prevent corrosive wear over long periods of operation. The unique detergent and dispersant additive system provides piston cleanliness and soot handling. This results in extreme reduction of both "hot" (piston lands and grooves, piston undercrown, purifier preheaters) and "cold" (crankcase, cambox, rocker area, fuel pumps, purifier bowl) deposits. Delo 1000 Maine lubricants provide a high degree of water tolerance and have good water separation.

Typical Characteristics

SAE Viscosity Grade MPID	30 219201	40 219200
Density at 15°C, kg/I (ASTM D4052)	0.9	0.9
Flash point, COC, °C (ASTM D92)	180 min	180 min
Pour point, °C (ASTM D97)	-12	-12
Kinematic Viscosity at 40°C, mm²/s (ASTM D445)	102	135
FZG test (A/8.3/90), failure load stage (CEC-L-07-95)	12	12

Recommended Applications

Delo 1000 Marine lubricants are recommended for medium-speed trunk piston diesel engines burning distillate and low sulfur fuels. The good load carrying capacity of Delo 1000 Marine lubricants also makes these suitable for use in engine reduction gears and other applications where EP properties are required. Delo 1000 Marine should be used in accordance with OEM guidelines and recommendations.

Delo 1000 Marine Lubricants Are Approved For:

MAN Energy Solutions	🗹 Daihatsu
🗹 🛛 Wärtsilä and MaK (Caterpillar)	🗹 Hyundai Himsen
🗹 Rolls Royce Bergen	🗹 Yanmar



Performance Benefits

1. Engine Protection

Controls cylinder liner wear effectively and helps to protect bearings from corrosion. High performance, antiwear additives provide protection against wear for cams, camshaft and bearings. Delo[®] 1000 Marine lubricants also promote a high degree of water tolerance and anti-foam protection.

2. Engine Cleanliness

Helps to ensure clean crankcases, piston interiors and lubricating oil lines.

3. Easy Purification

Effective water and contaminants handling.

4. Smooth Operation

Helps to provide minimum maintenance and downtime, long engine life and economical operating costs.



Disclaimer. Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturers so always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS. (March 2019)

© 2019 Chevron Marine Products LLC. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC or their respective owners.