



marine lubricants

Pinnacle[®] Marine Gear 220



Description

Pinnacle[®] Marine Gear 220 is a fully formulated, quality synthetic gear lubricant based on a mixture of polyalphaolefins and diesters. It offers oxidation stability at elevated temperatures, extended oil drain life and good wear protection.

Typical Characteristics

MPID	219401
Kinematic Viscosity at 40°C, mm ² /s	220.0
Kinematic Viscosity at 100°C, mm ² /s	22.7
Viscosity Index	115
Flash Point, °C	250
Pour point, °C (ASTM D97)	-45
Density, 15°C, Kg/l	0.89
FZG failure load stage, A/8.3/90	>12
FZG grey staining test, failure load stage	>10

Recommended Applications

Pinnacle Marine Gear 220 is recommended not only for lubricating plain and roller bearings, but also open and closed gears at high temperatures. It can be applied by bath, splash or circulation systems, and is specially targeted for the lubrication of purifier gears and reduction gears.

Pinnacle Marine Gear 220 Is Approved For:

Börger Pumps

Pinnacle Marine Gear 220 Meets The Requirements Of:

Various types of reduction gears Rolls-Royce Marine, Lohman-Stolterfoht Zollern Rope Winch, Ateck Bevel Gear, Kongsberg Winches

Elevators Ushio, Hyundai Elevator

Pinnacle Marine Gear 220 Is Suitable For Use In:

Centrifuges Alfa Laval, Westflia, Mitsubishi Kakoki

Inert gas blowers Robushi, Aalborg, Air products

Several deck applications where mineral gear oils cannot be used because of too high/low operating temperatures, or if extended drain intervals are required



marine lubricants

Performance Benefits**1. Thermal and Oxidation Stability**

Synthetic hydrocarbon base oils help to provide oxidation and thermal stability.

2. Bearing and Gear Protection

Bearing and gear protection combined with good copper compatibility at elevated temperatures were shown in the FZG test. Helps to protect against the formation of micro-pitting as a result of fatigue stress, as tested in the FZG grey staining test.

3. Compatibility

Compatible with most mineral oil-based EP and R&O gear lubricants, as well as with most PAO-based synthetic EP and R&O gear lubricants.

4. Low Friction

Unique low friction coefficient promotes improved gear efficiency, energy savings, less friction, less wear, and lower operating temperatures compared to conventional mineral oils.

5. Extended Drain Intervals

Aims to provide longer lubricant life, less maintenance costs, and less used oil disposal.



Disclaimer. Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturers so always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS. (September 2020)